


LR6-72PH 360~380M



**Hi-MO1 High Efficiency
Low LID Mono PERC Technology
(1500V Compatible)**

10-year Warranty for Materials and Processing;
25-year Warranty for Extra Linear Power Output



Complete System and Product Certifications

IEC 61215, IEC61730, UL1703
ISO 9001:2008: ISO Quality Management System
ISO 14001: 2004: ISO Environment Management System
TS62941: Guideline for module design qualification and type approval
OHSAS 18001: 2007 Occupational Health and Safety



* Specifications subject to technical changes and tests. LONGi Solar reserves the right of interpretation.

Positive power tolerance (0 ~ +5W) guaranteed

High module conversion efficiency (up to 19.6%)

Slower power degradation enabled by Low LID Mono PERC technology: first year <2%, 0.55% year 2-25

Better energy yield with excellent low irradiance performance and temperature coefficient

Solid PID resistance ensured by solar cell process optimization and careful module BOM selection

Adaptable to harsh environment: passed rigorous salt mist and ammonia tests


LONGi Solar

Room 201, Building 8, Sandhill Plaza, Lane 2290, Zuchongzhi Road, Pudong District, Shanghai, 201203
Tel: + 86-21-61047332 Fax: +86-21-61047377 E-mail: module@longi-silicon.com
Facebook: www.facebook.com/LONGi Solar

Note: Due to continuous technical innovation, R&D and improvement, technical data above mentioned may be of modification accordingly. LONGi Solar have the sole right to make such modification at anytime without further notice; Demanding party shall request for the latest datasheet for such as contract need, and make it a consisting and binding part of lawful documentation duly signed by both parties.

LR6-72PH 360~380M

Design (mm)



Mechanical Parameters

Cell Orientation: 72 (6×12)
Junction Box: IP67, three diodes
Output Cable: 4mm², 1200mm in length
Weight: 22.5kg
Dimension: 1956×991×40mm
Packaging: 26pcs per pallet

Operating Parameters

Operational Temperature: -40 °C ~ +85 °C
Power Output Tolerance: 0 ~ +5 W
Maximum System Voltage: DC1500V (IEC&UL)
Maximum Series Fuse Rating: 20A
Nominal Operating Cell Temperature: 45±2 °C
Application Class: Class A

Electrical Characteristics

Test uncertainty for Pmax: ±3%

Model Number	LR6-72PH-360M		LR6-72PH-365M		LR6-72PH-370M		LR6-72PH-375M		LR6-72PH-380M	
Testing Condition	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
Maximum Power (Pmax/W)	360	266.7	365	270.4	370	274.1	375	277.8	380	281.5
Open Circuit Voltage (Voc/V)	47.9	44.7	48.0	44.8	48.3	45.1	48.5	45.3	48.7	45.5
Short Circuit Current (Isc/A)	9.70	7.82	9.74	7.85	9.84	7.93	9.90	7.98	9.99	8.05
Voltage at Maximum Power (Vmp/V)	39.2	36.2	39.3	36.3	39.4	36.4	39.6	36.6	39.8	36.8
Current at Maximum Power (Imp/A)	9.18	7.36	9.29	7.45	9.39	7.53	9.47	7.59	9.55	7.66
Module Efficiency(%)	18.6		18.8		19.1		19.3		19.6	

STC (Standard Testing Conditions): Irradiance 1000W/m², Cell Temperature 25 °C, Spectra at AM1.5

NOCT (Nominal Operating Cell Temperature): Irradiance 800W/m², Ambient Temperature 20 °C, Spectra at AM1.5, Wind at 1m/s

Temperature Ratings (STC)


Temperature Coefficient of Isc	+0.057%/ °C
Temperature Coefficient of Voc	-0.286%/ °C
Temperature Coefficient of Pmax	-0.370%/ °C

Mechanical Loading


Front Side Maximum Static Loading	5400Pa
Rear Side Maximum Static Loading	2400Pa
Hailstone Test	25mm Hailstone at the speed of 23m/s

I-V Curve


Current-Voltage Curve (LR6-72PH-370M)



Power-Voltage Curve (LR6-72PH-370M)



Current-Voltage Curve (LR6-72PH-370M)



LONGi Solar

Room 201, Building 8, Sandhill Plaza, Lane 2290, Zuchongzhi Road, Pudong District, Shanghai, 201203
Tel: + 86-21-61047332 Fax: +86-21-61047377 E-mail: module@longi-silicon.com
Facebook: www.facebook.com/LONGi Solar

Note: Due to continuous technical innovation, R&D and improvement, technical data above mentioned may be of modification accordingly. LONGi Solar have the sole right to make such modification at anytime without further notice; Demanding party shall request for the latest datasheet for such as contract need, and make it a consisting and binding part of lawful documentation duly signed by both parties.